Delayed reservation decision in optical burst switching networks with optical buffers

G.M. Li^{*}, Victor O.K. Li⁺

^{*}School of Information Engineering
SHANDONG University at WEIHAI, China

⁺Department of Electrical and Electronic Engineering
The University of Hong Kong, Hong Kong, China

C.Y. Li, P.K.A. Wai

Photonics Research Center and Department of Electronic
and Information Engineering
The Hong Kong Polytechnic University
Hong Kong, China

Abstract—The proposed delayed reservation decision scheme offers the same node complexity as that in general OBS networks with optical buffers. Simulations show the proposed scheme has better performance than existing schemes in terms of burst loss probability.

Keywords- optical burst switching; Optical Buffer

I. INTRODUCTION

The massive explosion in Internet traffic has driven the development of wavelength division multiplexing (WDM) technology. Typically, the network is circuit-switched, with a lightpath (circuit) set up between the source and destination nodes, and an appropriate wavelength along the route is chosen. No optical buffer is needed at intermediate nodes. However, each fiber can only contain a limited number of wavelengths, and if two different lightpaths attempt to share one wavelength in a fiber, one of them must be blocked. Although wavelength converters can be used to decrease the blocking probabilities, the problem of wavelength allocation and routing is NP-hard [1]. Another drawback of wavelength routing is that it is not efficient for bursty data traffic since once a lightpath is set up, the bandwidth resource is dedicated to this lightpath, even if there is no traffic. To improve the bandwidth efficiency, IP over WDM using optical packet switching (OPS) becomes an ideal choice of the next generation networks. Ideally, all functions inside each node of an OPS network are performed in the optical domain [2], i.e., all-optical packet switching. However, optical processing capabilities are very limited and optical random access memory (RAM) is not available at present. In order to accommodate current technology, optical burst switching (OBS) was proposed in the late 1990s [3]. An OBS network consists of edge nodes at the periphery of the network, and core nodes inside the network. Edge nodes aggregate packets from upper layer into optical data bursts (DBs) and keep them in the optical domain. Each optical burst has an associated control packet (CP). CP is sent in a separate control channel and processed electronically [4,5] at each node, in an attempt to schedule its corresponding data burst.

In general OBS networks, nodes processing control packets (CPs) usually follow the *first-come-first-served* discipline; they can only know about previously scheduled data bursts (DBs), but cannot predict the information of incoming DBs. As a

consequence, this leads to inefficient resource utilization [6]. Similarly, although existing OBS networks with optical buffers [7-10] have buffered the CPs with the same delay of the DBs using fiber delay lines (FDLs) in order not to alter the offset between the CPs and the DBs, scheduling the DBs is still based on the arrival sequence of CPs. Thus, resource allocation is inefficient.

In this paper, we propose the delayed reservation decision (DRD) scheme in OBS networks with FDLs to improve the network performance. The remainder of this paper is organized as follows. In the second section, we briefly review optical burst contention resolution using FDLs and then present the proposed scheme. In the third section, we give numerical evaluations and we find that the proposed scheme has better performance than existing schemes. Finally, we conclude.

II. OBS NETWORKS WITH OPTICAL BUFFERS

A. General OBS networks with optical buffers

Although optical buffers are not mandatory in OBS networks, studies show that using FDLs as optical buffers can effectively improve the network performance [7, 10]. In an OBS network with FDLs, when a control packet cannot successfully reserve a wavelength at an output port for its corresponding data burst, it will try to reserve the available FDL with the shortest delay instead. There are two different node structures in OBS networks with FDLs: one is that each link has a dedicated FDL module [9], and we call it *FDL share per link*; the other is that each node has only one FDL module to be shared by all links [7], and we call it *FDL share per node*. The difference between *FDL share per link* and *FDL share per node* mainly lies in the hardware cost and the efficiency of FDL utilization. *FDL share per node* needs much less single FDL elements, and much less wavelength converters. But the tradeoff is that it needs more ports in the optical switch. Since wavelength converters are expensive, in terms of minimizing hardware cost, *FDL share per node* is a better choice since it is less bulky and utilizes FDLs more efficiently than *FDL share per link*.

To explain the operation of resolving contentions by FDLs, we consider a scenario in which each node has one output port with a single wavelength and a single FDL with fixed delay T_d ,

as shown in Figure 1. Suppose a new control packet CP_x arrives at the current node i . CP_x contains the information of its offset and its corresponding data burst length information T_{DB} . Based on these parameters, the expected data burst arriving time t_{st} and data burst departing time t_{en} ($t_{en} = t_{st} + T_{DB}$) can be obtained. After CP_x finishes its processing at time t_l , it attempts to reserve the wavelength at the output port from t_{st} to t_{en} . The reservation request for the interval (t_{st}, t_{en}) fails since it is blocked by an already scheduled data burst DB_0 , shown in Figure 1. Then, CP_x will check whether contention occurs in the data channel after delay T_d and whether the data burst can be accommodated in the FDL with the delay T_d . If both conditions are satisfied, CP_x will reserve the FDL for the interval (t_{st}, t_{en}) at a certain wavelength and reserve the data channel for the interval (t'_{st}, t'_{en}) simultaneously. When the data burst arrives at node i at time t_{st} , it will go through the FDL. Thus the data burst can be buffered for time T_d and the data burst is still kept in the optical domain and transmitted to the downstream nodes.

Figure 1. Chronological sequence of a straightforward approach in OBS networks with FDLs; contention occurs at node i , the updated control packet is sent out immediately after processing in this scenario.

When FDLs are used as optical buffers to resolve burst contentions in OBS networks, a straightforward option is to send the updated control packet to the downstream nodes immediately after the control packet successfully reserves resources in FDLs and data channel for its corresponding data burst. As shown in Figure 1, after CP_x successfully resolves contention using FDL at node i , CP_x is updated with the new information of the delayed data burst and sent to the downstream node immediately. The offsets at all downstream nodes will be changed according to the FDL delay at node i .

Previous work [4, 7-9] note that a burst with longer offset time has lower dropping probability. FDLs help to improve performance in the extended-offset based quality of service (QoS) provision schemes. Most existing work in OBS networks focus on the general scheme as shown in Figure 2. In order to keep the burst priority unchanged, the corresponding burst offset value must be the same as in the scenario without FDLs. This implies that, after CP_x successfully resolves contention using FDL at node i , the control packet must be electronically buffered with the same delay as that of the suitable FDL. Under the general reservation scheme in OBS networks with FDLs [7, 8], the decision of the network resource allocation is made immediately after processing the CP. For the example shown in

Figure 2, resource allocation decision is done at t_l , but CP_x has to be electronically buffered with the same delay, T_d , as the desired FDL; the updated control packet, CP'_x , is sent to the downstream node at t'_l . By comparison, the straightforward scheme is more cost-efficient in hardware than the general scheme since it does not need extra electronic buffer for the control packets. Its drawback is that it cannot be implemented to provide quality of service (QoS) in the extended-offset scheme since changing offsets will change the priority of the corresponding data bursts.

Figure 2. The chronological sequence of burst contention resolution using FDLs in a node with a single wavelength and a single FDL; contention occurs at node i , the updated control packet is electronically buffered with T_d after processing in this scenario.

B. Delayed reservation scheme

The *first-come-first-served* discipline leads to inefficient resource utilization in general OBS networks [6,11]. In most existing work on OBS network with FDLs, control packets are electronically buffered with the same delay as the data bursts using FDLs, and scheduling data bursts in FDLs and data channels is still based on the arrival sequence of control packets. Thus, the resource allocation is still inefficient.

Figure 3 illustrates an example of the inefficient resource allocation in the general OBS networks with FDLs due to the *first-come-first-served* discipline. We assume each node in a general OBS network has a fiber with a fixed delay T_d to resolve burst contentions. We further assume that a node has received three control packets, $c1$, $c2$, and $c3$, which request the same output port O_l with wavelength channels $D1$ and $D2$. Their corresponding data bursts are marked $B1$, $B2$, and $B3$ following their corresponding control packets. $c1$, $c2$, and $c3$ finish their processing at times t_1 , t_2 and t_3 respectively. We assume that, due to the burst contention at the output port, all three data bursts, $B1$, $B2$, and $B3$, need to be buffered by the FDL. According to the reservation scheme in general OBS networks with FDLs, control packets $c1$, $c2$ and $c3$ need to be electronically buffered until t_3 , t_6 and t_7 ; then their updated corresponding control packets $c1'$, $c2'$ and $c3'$ are sent to the downstream nodes. The actual time of arrival of $B1$, $B2$, and $B3$ at the output port are t_8 , t_{11} and t_{10} respectively. A new incoming control packet, $c4$, arrives at the node at t_4 and its data burst $B4$ arrival time is t_9 as shown in Figure 3(a).

Follows the common reservation scheme of the general OBS networks with FDLs, the scheduling decisions are made

as following: $c1$ arrives at the node at t_1 and its data burst encounters burst contention. $c1$ finds that $B1$ can be scheduled at time t_8 and there is no burst contention at the desired FDL; thus, after finishing processing $c1$ at t_1 , control packet $c1$ is buffered electronically for an interval $T_d = t_5 - t_1$ and the updated control packet $c1'$ is sent to the downstream node at t_5 . The delayed data burst is scheduled at t_8 . Control packets $c2$ and $c3$ are processed likewise. To minimize the idle periods between data burst transmissions, $B2$ is scheduled on channel $D1$ with starting time t_{11} after its control packet finishes processing and makes scheduling decision at t_2 . Consequently, $B3$ is assigned channel $D2$ with starting time t_{10} and its scheduling decision is made at t_3 . When $c4$ arrives at the node, it finds its data burst $B4$ can not be scheduled on any channel due to the burst contention, as shown in Figure 3(b). Thus, FDLs or other contention resolutions have to be used; otherwise, data burst $B4$ will be dropped. However, even after delay T_d , no data channel is available to accommodate the data burst $B4$, as shown in Figure 3(c). Ultimately, $B4$ is dropped.

Figure 3. (a) The arrival and departure sequence of control packets and the corresponding data bursts, (b) channel assignment according to the reservation scheme in general OBS with FDLs; the new incoming data burst cannot be scheduled directly, (c) the new incoming data burst cannot be scheduled after delay T_d .

Under the general reservation scheme in OBS networks with FDLs, we notice that, after control packets successfully resolve contention using FDLs, they have to be electronically buffered with the same delay as the selected FDLs. In fact, the decision of the network resource allocation is made immediately after processing the control packet. The process of electronic buffering does not contribute to the network performance. Hereby, we propose the delayed reservation decision (DRD) scheme.

The proposed scheme takes advantage of the process of electronic buffering of control packets with the aim to improve the resource utilization efficiency. As shown in Figure 2, under the proposed scheme, rather than making resource allocation decision after processing CP_x at time t_1 , the reservation decision is made just before sending out the updated control

packet, CP_x' , i.e., at time $(t_1' - T_0)$, where T_0 is the transmission time of the control packet. The transmission time T_0 is hardware dependent. We can assume that it is a constant value at each node, and it is usually negligible compared to the duration of scheduling. The procedure of the proposed scheme is as follows: after receiving a control packet, the control unit at the node performs processing control packet. At time t_1 , the scheduling decision is not really made, but virtually; i.e., the virtual scheduling decision does not reserve any network resources but marks the interval to indicate that the interval may be used for a data burst. Before the electronically buffered control packet is sent to the downstream node, the scheduling decision is really made at time $(t_1' - T_0)$. During the period from t_1 to $(t_1' - T_0)$, the channel assignment is based on the order of data burst arrival sequence. Since the control unit at node i can gather more information from arriving control packets, a better scheduling decision may be made and the network resource can be used more efficiently. Since more information of the subsequent DBs is available to the node, better resource allocation can be achieved. Many sophisticated scheduling schemes of the DBs in FDLs are possible with the proposed scheme. In this paper, however, the DBs in the FDLs are scheduled only according to their actual arrival sequence to demonstrate the principle of the DRD scheme.

Figure 4. (a) The arrival and departure sequence of control packets and the corresponding data bursts, (b) at t_1 , $B1$, $B2$ and $B3$ are virtually scheduled at the output port, (c) at $(t_1' - T_0)$, $B1$, $B2$ and $B3$ are re-scheduled according to the burst arrival sequence, and the ultimate scheduling decision of $B1$ is made, (d) the ultimate scheduling decisions of $B1$, $B2$ and $B3$ when $C4$ arrives.

Figure 4 shows that the proposed scheme can achieve better resource allocation than the general reservation scheme as illustrated in Figure 3. After processing $c1$ at t_1 , $c1$ is electronically buffered until t_5 and its corresponding data burst $B1$ is virtually scheduled on channel $D1$. $c2$ and $c3$ are

processed in the same way. Thus, after t_3 , $B1$, $B2$ and $B3$ are virtually scheduled at the output port as shown in Figure 4(b). This virtual scheduling follows the arrival sequence of control packets and has a similar channel assignment as the general reservation scheme. At time $(t_1 - T_0)$, ahead of sending the updated control packet $c1'$ to the downstream node, the ultimate scheduling decision of $B1$ is made. Based on the virtual scheduling, $B1$, $B2$ and $B3$ are re-scheduled according to the burst arrival sequence. Therefore, $B1$ is finally scheduled on channel $D1$, $B3$ is virtually scheduled on channel $D1$ too and $B2$ is virtually scheduled on channel $D2$ as shown in Figure 4(c). The ultimate scheduling decision of $B2$ and $B3$ follows a similar process. Consequently, $B1$ and $B3$ are scheduled on $D1$, and $B2$ is scheduled on $D2$. When $c4$ arrives at the node, it can successfully schedule its data burst $B4$ on channel $D2$ without burst contention resolutions, as shown in Figure 4(d).

III. PERFORMANCE EVALUATION

Following the common simulation assumptions [11], the input network traffic is in the form of data bursts and follows the Poisson distribution. The data burst length is an exponential distribution. The average control packet processing time is assumed to be one tenth of the average data burst transmission time. We assume that each link has one dedicated wavelength as the control channel and ten wavelengths for carrying data bursts. Each node in the topology may be an edge node or a core node, and full wavelength conversion capability is available at each node. When a new data burst arrives at an edge node, it randomly chooses a destination from the rest of the nodes in the network and the shortest path routing algorithm is used. All nodes are assumed to receive the same offered load in the network.

Figure 7 gives the performance comparison in loss probability of the delayed reservation decision scheme and the VFO scheme [11]. The VFO scheme, plotted in dotted lines, buffers each incoming data burst with a fixed delay, and thus the *FDL share per link* architecture must be deployed. The DRD scheme, deploying the *FDL share per node* architecture, is plotted in solid lines. The lines with squares and crosses indicate that each node has an FDL with a fixed delay of one time of the control packet processing time, i.e., 0.1 time units. Those with circles and asterisks indicate that each node has an FDL with a fixed delay of ten times of the control packet

processing time. We observe that, only when the network load is high, will VFO scheme have lower burst loss probability. VFO uses FDL to delay data bursts, and the scheduler can resort data bursts according to their arrival times in order to utilize bandwidth more efficiently. When the network offered load is high, FDL buffers in both VFO and DRD are filled with data bursts. In VFO, the interval to optimize scheduling is fixed at B . In DRD, the interval is dependent on the delay required to resolve burst contention, which is less than B in most cases. Therefore, VFO has lower burst loss probability when the network is heavily loaded. While the network is not highly loaded, for example when the load is less than 0.8 with buffer of one time unit delay, the DRD scheme has much lower loss probability than the VFO scheme. This is due to the fact that VFO buffers each incoming data burst and the burst contention may not be effectively resolved.

Figure 7. The loss probability of the general OBS with FDLs and the DRD scheme.

IV. CONCLUSIONS

Based on existing OBS networks with optical buffers, we propose the delayed reservation decision scheme to enhance the network performance. The proposed scheme has the same hardware complexity at each node as the existing OBS networks with optical buffers, but allows extra electronic processing of control packets to utilize the network resources more efficiently. Compared to other delayed reservation

schemes such as the virtual fixed offset time, the proposed DRD scheme decreases the hardware complexity, and improves the network performance in loss probability when the network is not highly loaded.

ACKNOWLEDGMENT

This research is supported in part by the Areas of Excellence Scheme established under the University Grants Committee of the Hong Kong Special Administrative Region, China (Project No. AoE/E-01/99). Additional support is provided by a grant from The Hong Kong Polytechnic University (Project Number A-PF98).

REFERENCES

- [1] K. C. Lee and V. O. K. Li, "A wavelength-convertible optical network," *Journal of Lightwave Technology*, vol. 11, no. 5, pp. 962-970, 1993.
- [2] X. C. Yuan, V. O. K. Li, C. Y. Li, and P. K. A. Wai, "A novel self-routing address scheme for all-optical packet-switched networks with arbitrary topologies," *Journal of Lightwave Technology*, vol. 21, no. 2, pp. 329-339, 2003.
- [3] M. Yoo and C. Qiao, "Just-Enough-Time (JET): A High Speed Protocol for Bursty Traffic in Optical Networks," in *IEEE/LEOS Technologies for Global Information Infrastructure 1997*, pp. 26-27, 1997.
- [4] C. Qiao and M. Yoo, "Optical burst switching (OBS) - a new paradigm for an optical Internet," *Journal of High Speed Networks*, vol. 8, no. 1, pp. 69-84, 1999.
- [5] M. Yoo, M. Jeong, and C. Qiao, "A high-speed protocol for bursty traffic in optical networks," in *SPIE Proceedings, All Optical Communication Systems: Architecture, Control and Network Issues*, pp. 3230, 1997.
- [6] C. Y. Li, G. M. Li, P. K. A. Wai, and V. O. K. Li, "Novel resource reservation schemes for optical burst switching," in *Proceedings of IEEE ICC 2005*, 3ed, pp. 1651-1655, 2005.
- [7] Y. Xiong, M. Vandenhoude, and H. C. Cankaya, "Control architecture in optical burst-switched WDM networks," *IEEE Journal on Selected Areas in Communications*, vol. 18, no. 10, pp. 1838-1851, 2000.
- [8] M. Yoo, C. Qiao, and S. Dixit, "The effect of limited fiber delay lines on QoS performance of optical burst switched WDM networks," in *Proceedings of IEEE ICC 2002*, 2ed, pp. 974-979, 2000.
- [9] M. Yoo, C. Qiao, and S. Dixit, "QoS performance of optical burst switching in IP-over-WDM networks," *IEEE Journal on Selected Areas in Communications*, vol. 18, no. 10, pp. 2062-2071, Oct. 2000.
- [10] X. Lu and B. L. Mark, "Performance modeling of optical-burst switching with fiber delay lines," *IEEE Transactions on Communications*, vol. 52, no. 12, pp. 2175-2183, 2004.
- [11] J. Li, C. Qiao, J. Xu, and D. Xu, "Maximizing throughput for optical burst switching networks," in *Proceedings of IEEE INFOCOM 2004*, 3ed, pp. 1853-1863, 2004.